

2" FLOWMETER

MODEL HO2X2-25-CB-1MX-NPT-X TOTALIZER MODEL HIT-2A-3-A-X-X-FX-X

FEATURES:



REPEATABLE FLOW RANGE: 56.8 LPM - 852 LPM (51 m3/h)
REPEATABILITY: +/- 0.25% OF READING OVER THE REPEATABLE FLOW RANGE.
CONSTRUCTION: 316 STAINLESS STEEL WITH 17.4 PH ROTOR..
END FITTING: MALE NATIONAL PIPE THREAD

BEARINGS: CERAMIC HYBRID BALL BEARING, SELF LUBRICATING
PICKUP COIL: MAGNETIC TYPE.
CALIBRATION: SUPPLIED WITH CALCULATED K-FACTOR BASED ON TEN POINT WATER CALIBRATION AND ACCURATE TO +/- 2%.

HIT-2A TOTALIZER/FLOW RATE INDICATOR

- 5 DIGIT RATE DISPLAY, 8 DIGIT TOTALIZER DISPLAY.
- ISOLATED SCALED PULSE OUTPUT.
- RS 232 PORT FOR CONFIGURATION AND MONITORING.
- PASSWORD PROTECTION FOR MENU AND RESET.

ENCLOSURE STYLE:

EX-PROOF ENCLOSURE. COMPLIANCE & CERTS FOR ENCLOSURE AS FOLLOWS:

NEC/IEC: CLASS I, DIV 1 & 2, GROUPS B, C, & D; CLASS II, DIV 1, GROUPS

E, F, & G; CLASS II, DIV 2, GROUPS F & G; CLASS III.

INPUT POWER : INTERNAL BATTERIES (TWO EACH EXPLOSION-PROOF STYLE 3 ENCLOSURES MOUNTED ON TURBINE.

Port Gentil:

juan.Guerrero@ois-group.com
olivier.vacher@ois-group.com
bert.bouchard@ois-group.com

Pointe Noire:

jean-pierre.lafont@ois-group.com
ignacio-guerrero@ois-group.com

www.ois-group.com