

# MYERS D 65- 20 TRIPLEX ELECTRIC PUMP

## FEATURES :



| D65-20 | Piston Size In.     | Max. PSI | *Gallon Per/Rev | 1000 RPM US GPM | 1200 RPM US GPM | 1400 RPM US GPM | 1600 RPM US GPM | 1800 RPM US GPM | Flows: 38 – 69 GPM<br>PSI: 1000 – 2000<br>Stroke Length: 3.75" | Max. HP 95 |
|--------|---------------------|----------|-----------------|-----------------|-----------------|-----------------|-----------------|-----------------|--|------------|
|        | 2.000               | 2000     | .0387           | 38.7            | 46.4            | 54.1            | 61.9            | 69.6            |  |            |
|        | HP Required @ RPM** |          |                 | 53.1            | 63.6            | 74.2            | 84.9            | 95.0            |  |            |

- SKID MOUNTED FOR TRANSPORT AND FASTENING



- **ELECTRIC MOTOR :**



**Port Gentil:**

[juan.Guerrero@ois-group.com](mailto:juan.Guerrero@ois-group.com)  
[olivier.vacher@ois-group.com](mailto:olivier.vacher@ois-group.com)  
[bert.bouchard@ois-group.com](mailto:bert.bouchard@ois-group.com)

**Pointe Noire:**

[jean-pierre.lafont@ois-group.com](mailto:jean-pierre.lafont@ois-group.com)  
[ignacio-guerrero@ois-group.com](mailto:ignacio-guerrero@ois-group.com)

[www.ois-group.com](http://www.ois-group.com)